# UTILITY

+

Attorney Docket No.	169.1327 CIP
First Name	d Inventor or Application Identifier
EDWIN HO	
Express Mail Label No.	

重ご	LAILINI ALLEIGAI	1014	-		i ii st I Valiliet	I IIIVeritor or Applic	auon identiner	
	₩ TRANSMITTAL		EC	OH NIWC				
■ c(Onl)	y for new nonprovisional applications unde	er 37 CFR 1.53(b))		press Mail L	abel No.			
P See	APPLICATION ELEMI MPEP chapter 600 concerning utility pater			ADDR	ESS TO:			atents
1.	Fee Transmittal Form (Submit an original, and a duplicate fo			6.	Microfiche (	Computer Program		903
2. X 3. X 4. X	Specification	heets 6			a. O	mino Acid Sequenessary) Computer Readable Paper Copy (identic	e Copy cal to computer co	
1	a. Newly executed (original or	copy)	ſ		ACCOM	PANYING APPLIC	ATION PARTS	
1			ŀ					
And these the Constitution and the Constitution and the Constitution of the Constituti	b. X Unexecuted for information purposes c. Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below]  1. DELETION OF INVENTOR(s) Signed Statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)2 and 1.33(b) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4c, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.			8.	37 CFR 3.73 (when there English Tra Information Statement In Preliminary Return Rec (Should be	(IDS)/PTO-1449  Amendment  eipt Postcard (MPI specifically itemize	Power  (if applicable)  Copies  Citatio	
20.00				14.	Small Entity Statement(		ent filed in prior app still proper and desi	
				15.		opy of Priority Docu riority is claimed)	iment(s)	
				16.	Other:			
17. lf:	a CONTINUING APPLICATION, check and Continuation Divisional			•		lication No. 09/32	6,561 filed June	7, 1999
		18. CORRES	PONE	DENCE ADD	RESS			
x	Customer Number or Bar Code Label	(Insert Customer No.	055 or Atta		abel here)	or Corres	pondence address	below
NAME								
<u> </u>								
Addres	38							
City		State				Zip Code		
Countr	у	Telephone				Fax		

1	N "10
140	W. 16
p	27
1	1
1	
0.00	15 H
S 21.00	5 8 4 TB
9	72
IR willer	N.
į.	
See Mente	44
84.46	Š
· Ju	1
4	P

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS		
	TOTAL CLAIMS (37 CFR 1.16(c))	70-20 =	50	X \$ 18.00 =	\$ 900.00		
	INDEPENDENT CLAIMS (37 CFR 1.16(b))	6-3 =	3	X \$ 78.00 =	\$ 234.00		
	MULTIPLE DEPENDEN	T CLAIMS (if applicable) (37	CFR 1.16(d))	\$260.00 =	\$ 260.00		
				BASIC FEE (37 CFR 1.16(a))	\$ 760.00		
			Total of	above Calculations =	\$2154.00		
	Reduction by						
		\$2154.00					
a. b. c. 20.	A Small entity statement is enclosed  A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.  Is no longer claimed.  X  A check in the amount of \$ \$2154.00 to cover the filing fee is enclosed.						
1.	A check in the am-	ount of \$ to c	over the recordal fee is	enclosed.			
2. Th	he Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account to 06-1205;						
a.	X Fees req	Fees required under 37 CFR 1.16.					
b.		Fees required under 37 CFR 1.17.					
C.	Fees req	uired under 37 CFR 1.18.					

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED			
NAME	Leonard P. Diana (Reg. No. 29,296)		
SIGNATURE	LP.2		
DATE	December 7, 1999		

/PAP

NY\_MAIN 46129 v 1

10

15

20

25

## FACE DETECTION IN DIGITAL IMAGES

#### Technical Field of the Invention

The present invention relates to digital colour images and, in particular, to the detection of faces in colour digital images.

### Background Art

Colour digital images are increasingly being stored in multi-media databases, and utilised in various computer applications. In many such applications it is desirable to be able to detect the location of a face in a visual image as one step in a multi-step process. The multi-step process can include content-based image retrieval, personal identification or verification for use with automatic teller machines or security cameras, or automated interaction between humans and computational devices.

Various prior art face detection methods are known including eigenfaces, neural networks, clustering, feature identification and skin colour techniques. Each of these techniques has its strengths and weaknesses, however, one feature which they have in common is that they are computationally intensive and therefore very slow, or they are fast but not sufficiently robust to detect faces.

The eigenface or eigenvector method is particularly suitable for face recognition and there is some tolerance for lighting variation, however it does not cope with different viewpoints of faces and does not handle occlusion of various facial features (such as occurs if a person is wearing sunglasses). Also it is not scale invariant.

The neural network approach utilises training based on a large number of face images and non-face images and has the advantages of being relatively simple to implement, providing some tolerance to the occlusion of facial features and some tolerance to lighting variation. It is also relatively easy to improve the detection rate by re-training the neural network using false detections. However, it is not scale invariant.

10

15

20

25

does not cope with different viewpoints or orientation, and leads to an exhaustive process to locate faces on an image.

The clustering technique is somewhat similar to the eigenface approach. A pixel window (eg. 20 x 20) is typically moved over the image and the distance between the resulting test pattern and a prototype face image and a prototype non-face image is represented by a vector. The vector captures the similarity and differences between the test pattern and the face model. A neural network can then be trained to classify as to whether the vector represents a face or a non-face. While this method is robust, it does not cope with different scales, different viewpoints or orientations. It leads to an exhaustive approach to locate faces and relies upon assumed parameters.

The feature identification method is based upon searching for potential facial features or groups of facial features such as eyebrows, eyes, nose and mouth. The detection process involves identifying facial features and grouping these features into feature pairs, partial face groups, or face candidates. This process is advantageous in that it is relatively scale invariant, there is no exhaustive searching, it is able to handle the occlusion of some facial features and it is also able to handle different viewpoints and orientations. Its main disadvantages are that there are potentially many false detections and that its performance is very dependent upon the facial feature detection algorithms used.

The use of skin colour to detect human faces is described in a paper by Yang J and Waibel A (1995) "Tracking Human Faces in Real-Time" CMU-CS-95-210, School of Computer Science, Carnegie Mellon University. This proposal was based on the concept that the human visual system adapts to different levels of brightness and to different illumination sources which implies that the human perception of colour is consistent within a wide range of environmental lighting conditions. It was therefore thought

10

15

20

possible to remove brightness from the skin colour representation while preserving accurate, but low dimensional, colour information. As a consequence, in this prior art technique, the chromatic colour space was used. Chromatic colours (eg. r and g) can be derived from the RGB values as:

$$r = R / (R + G + B)$$
 and  $g = G / (R + G + B)$ 

These chromatic colours are known as "pure" colours in the absence of brightness.

Utilising this colour space, Yang and Waibel found the distribution of skin colour of different people, including both different persons and different races, was clustered together. This means that the skin colours of different people are very close and that the main differences are in differences of intensity.

This prior art method first of all generated a skin colour distribution model using a set of example face images from which skin colour regions were manually selected. Then the test image was converted to the chromatic colour space. Next each image in the test image (as converted) was then compared to the distribution of the skin colour model. Finally, all skin colour pixels so detected were identified, and regions of adjacent skin colour pixels could then be considered potential face candidates.

This prior art method has the advantage that processing colour is much faster than processing individual facial features, that colour is substantially orientation invariant and that it is insensitive to the occlusions of some facial features. The system is also substantially viewpoint invariant and scale invariant. However, the method suffers from a number of disadvantages including that the colour representation of the face can be influenced by different lighting conditions, and that different cameras (eg. digital or film) can produce different colour values even for the same person in the same environment.

10

15

20

1

However a significant disadvantage of the prior art methods is that the skin colour model is not very discriminating (ie. selecting pixels on a basis of whether they are included in the skin colour distribution results in a lot of non-skin colour pixels being included erroneously). It is also difficult to locate clusters or regions of skin colour pixels that can be considered as candidate faces.

#### Disclosure of the Invention

An object of the present invention is to provide an improved method of detecting one or more faces in digital colour images.

In accordance with a first aspect of the present invention there is disclosed a method of detecting a face in a colour digital image formed of a plurality of pixels, said method comprising the steps of:

- testing the colour of said pixels to determine those said pixels having predominantly skin colour, said testing utilising at least one image capture condition provided with said image; and
- (ii) subjecting only said those pixels determined in step (i) as having predominantly skin colour to further facial feature analysis whereby those said pixels not having a predominantly skin colour are not subjected to said further facial feature analysis.

Preferably each image capture condition is acquired at a time the image is captured. Advantageously, the image is encoded according to a predetermined format and at least one image capture condition is represented as meta-data associated with the format. Most preferably the at least one image capture condition comprises lighting conditions at a time the image was captured.

In a particular implementation step (i), comprises the sub-step, preceding said 25 testing, of:

5

 (a) dividing said image into a plurality of regions, each said region comprising a plurality of said pixels: and

wherein said testing is performed on pixels within each said region to determine those ones of said regions that are predominantly skin colour and step (ii) comprises performing said further facial feature analysis on only those said regions determined to be predominantly of skin colour.

In accordance with another aspect of the present invention, there is disclosed a method of detecting a face in a colour digital image, said method comprising the steps of.

- segmenting said image into a plurality of regions each having a
   substantially homogenous colour;
  - (ii) testing the colour of each said region created in step (i) to determine those regions having predominantly skin colour; and
  - (iii) subjecting only the regions determined in step (ii) to further facial feature analysis whereby said regions created in step (i) not having a predominantly skin colour are not subjected to said further feature analysis.

Apparatus and computer readable media for performing the invention are also disclosed

#### Brief Description of the Drawings

A number of embodiments of the present invention will now be described with 20 reference to the drawings in which:

- Fig. 1 is a schematic representation of the pixels of a colour digital image;
- Fig. 2 shows the segmenting of the image of Fig. 1 into a plurality of regions each having a substantially homogenous colour according to a first embodiment;
- Fig.  $3^{i}$  is a flow chart of a face detection process according to the first 25 embodiment;

20

25

5

Fig. 4 is a schematic block diagram of a general purpose computer upon which embodiments of the present invention can be practised;

Fig. 5 is a flow chart depicting the generation of a face colour distribution model:

Fig. 6 is a flow chart of a face detection process according to a second embodiment; and

Fig. 7 is a flow chart of a face detection process according to a third embediment.

## Detailed Description including Best Mode

Fig. 1 illustrates a typical colour digital image 1 having a size of 832 x 624 10 pixels 5, each of which has an RGB value.

According to a first embodiment of the present invention, rather than consider the skin colour of the image on a pixel by pixel basis as described above in relation to the prior art of Yang and Waibel, the image 1 is segmented into a number of regions. An example of such segmentation is schematically illustrated in Fig. 2 on the segmentation basis that all the pixels in each region 2 have substantially the same colour. Alternatively the image may be segmented into arbitrary regions for processing.

The first embodiment implements a process 30 illustrated in the flow chart of Fig. 3, in which the regional segmentation of the image is carried out at step 31. Next, the regions of the image are converted in step 32 into the chromatic colour space (as described above). The next step 33 is to select those of the regions determined in step 31 which have a specified percentage (typically in the range 90-95%) of pixels having a skin colour. These selected regions are then conveniently represented by a boundary box or other boundary indication. Finally, at step 34 the selected regions, including any combinations of overlapping regions, are subjected to a further analysis (preferably not based on skin colour) to determine if the selected region(s) represent a face or faces.

10

15

20

25

This initial colour grouping can use any region based colour image segmentation technique. Preferably the image is partitioned into colour regions by seeking connected groups of pixels which have similar colours over a local region. Very small isolated initial spatial groupings can be ignored in order to find major colour regions and reduce a noise effect. A representative colour of each initial spatial region is determined by an average colour value of the region.

A colour region starts from an arbitrarily chosen pixel, which is compared with its neighbouring pixels. The region size is increased by adding neighbouring pixels, which are similar in colour, using a colour similarity threshold T A neighbouring pixel is added to the region if |Rp-Rm|<T and |Gp-Gm|<T and |Bp-Bm|<T, where Rp, Gp, Bp are R, G, B values of the neighbouring pixel and Rm, Gm, Bm represented average R, G, B values of the region.

When a region has no more neighbouring pixels of similar colour, the region stops growing and represents one of the initial spatial groupings. If the region size is below a predetermined threshold value, it is ignored. A region having a pixel number equal or greater than the predetermined threshold is represented by its average colour.

A new pixel which does not yet belong to any region is chosen to start a new colour region. The process continues until each pixel in the image either belongs to an initial spatial grouping or has been ignored as being part of a small region.

The initial spatial groupings provide a colour region segmentation of the image with each region being represented by its average colour.

In this way, for most images where the bulk of the image is not a face, or part of a face, the majority of pixels will be grouped into regions or objects (be they foreground or background, etc.) which are clearly not faces. Therefore these non-facial objects can be quickly eliminated on the basis of their colour.

10

15

20

25

Once the regions have been determined, they are then converted into the "pure" chromatic colour space utilising the equations given above so as to provide r and g values. A generous rule such as a rule that at least 85% of the pixels within a given region be of face colour can be used to select those regions worthy of further examination. Preferably, the test for face colour takes into account the nature of the original image, for example whether the image was taken with or without a flash. This information can be determined from the image source, ee, a camera.

Thereafter, only those selected regions are subjected to a further test to determine the presence of facial features. This further test provides a conclusive determination as to whether or not a region constitutes a face. In this connection, the further test is likely to be computationally slower and therefore the above described elimination of regions ensures that the computationally slow method is only applied to relatively small portions of the overall image. Thus the total processing time is reduced. Accordingly, the above method performs a computationally simple process on most, if not all pixels, and then only performs complex examination on skin colour regions.

The preferred method of verifying if a region represents a face relies upon edge detection techniques as a means of detecting facial features. In particular facial features such as eyes, eyebrows and mouths often appear as dark bars on a face and thus provide dark edges.

The preferred form of edge detection is use of an edge detection filter. This utilises two functions operating in orthogonal directions. To detect a horizontal bar a second derivative Gaussian function is used in the vertical direction and a Gaussian function is used in the horizontal direction.

Once an edge has been determined in this way each detected edge is examined.

Any pair of detected edges can be found to be derived from, and thus be indicative of, a

10

15

20

25

pair of eyes, a pair of eyebrows, or an eye and associated eyebrow, depending upon the relative position and size of the detected edges. Similarly, an individual edge can be derived from, and thus be indicative of, a mouth if it is located at an appropriate position relative to the eves and/or evebrows already detected.

By proceeding in this fashion, a given region begins to accumulate facial features building from skin tone through eyebrows/eyes and then to a mouth. The more facial features found for a given region which is a face candidate, the greater the possibility that the candidate actually is a face.

Furthermore, the above described method has the advantage that it is able to cater for the circumstance where a face is backgrounded against a background region of substantially the same colour. Under these circumstances, in Yang and Waibel's method, no boundary between the face and the background would be likely to be detected. Therefore the region as a whole would be selected for further testing. However, the above method utilises the full colour space to segment the image, before making decisions about which pixels are skin colour. Consequently the face is more likely to be separated from the background. In addition, the method is naturally independent of orientation or partial occlusion of the face.

Furthermore, the above method also permits false positives to be examined at the further stage and therefore does not exclude from subsequent testing regions which are likely to be ultimately determined as a facial region.

The first embodiment described above notes that the nature of the original image may be taken into account when performing an initial face detection process. Further embodiments to be now described build upon this feature.

When an image is captured using a camera it is necessary either for the person taking the picture to manually establish the camera settings (such as shutter speed,

15

20

25

aperture, focal length, etc), or for the camera to perform this operation automatically. Whichever is the case, the settings of the camera directly effect the appearance and quality of the image taken. In particular, the perceived brightness, colour, and sharpness of the objects within an image all depend on how the settings of the camera are configured. For example, it is possible to take two pictures of the same scene with different camera settings and to obtain two images in which the same objects appear with different colours and brightness. Therefore, the ability to calibrate (in particular) colour information contained in (digital) images enables a broad variety of object detection and classification tasks in which colour is a strong discriminating feature.

Face detection is one such example application, and the present inventors have determined that the creation of face colour distribution models (CDM's), each adapted to specific lighting conditions, that can improve both the accuracy and reliability of face detection. Variations in lighting conditions can result from the use of a flash, such being a feature recognised as contributing in the face detection method of the first embodiment. Since lightness is representative of colour features such as luminance and chrominance, such features may be used to quantify face detection.

Before an image can be processed using a face colour distribution model, the face colour distribution model must be constructed. This is performed according to a method 50 shown in Fig. 5. The method 50 firstly gathers image samples at step 52 that are representative images that contain faces, the images being acquired under a variety of lighting conditions and thus indicative of changes in luminance and chrominance. These images are then manually examined in step 54 to extract regions of skin colour for further processing in model formation. Step 54 may be performed by manually drawing a bounding box around a sample of face coloured pixels. Step 56, which follows, derives colour representation values for the extracted pixels. This may be performed by

10

15

20

25

transforming the extracted pixels into a perceptual colour space such as CIE L\*u\*v or CIE L\*a\*b, so that each pixel is represented by at least a 2-dimensional vector. Alternatively other colour spaces such as HLS and HSV may be used. Preferably each pixel is represented as a length-3 vector incorporating both the luminance and chrominance values.

The colour representation values of pixels are then divided at step 58 into a number of sets (58a, 58b ... 58n) according to the lighting conditions present when each of the images were captured. Example sets are flash, non-flash, indoor, outdoor, and combinations of these. Alternatively, lighting parameters obtained directly from the camera such as the operation of a flash, may be used to identify and distinguish the sets. Other lighting conditions such as bright or cloudy, dusk or dawn, or a type of artificial light such as fluorescent, incandescent or halogen, may be used or detected for these purposes. These details may be provided by means of human input at the time of image capture.

For each of the sets (58a ... 58n) of face samples, step 60 then constructs a corresponding colour distribution model (CDM) (60a ... 60n) that best fits the samples of face colour pixels. The CDM can be a histogram, a probability density function, or a binary map. In one embodiment, a mixture of Gaussian PDF's are fit to the sample data using techniques known in the art such as the expectation maximisation (EM) algorithm, with either cross-validation, jackknife, and bootstrap techniques being used to estimate the goodness of fit of the model.

When each CDM (60a ... 60n) has been constructed, it is then desirable as shown in step 62 to establish a corresponding probability threshold (62a ... 62n) below which a colour vector is to be classified as relating to a non-face pixel, and above which the colour vector is to be classified as a potential face pixel. Additionally, the face colour

10

15

20

25

probability can be used directly in further facial image analysis steps detailed below. In the preferred embodiment, the CDM is constructed from colour representation values derived using a perceptual colour space (such as CIE L\*u\*v or CIE L\*a\*b) and then transformed back into the colour format of the input image, ie., either RGB or YUV. This removes the necessity for transforming the input image into the perceptual colour space.

Since different image capture devices have differing performance, often determined by the quality and size of optical components (eg. lens, mirrors, aperture etc.), typically a CDM or a set of CDM's are generated for a particular capture device. In one implementation, where the image capture device (eg. camera) includes a light meter, a reading from the light meter at the moment the image was captured can be used to determine the required CDM. In this fashion, a greater range of colour models may be devised and can be selected without possible human interference. Such interference may occur where the human user manually selects the operation of the flash where otherwise automatic operation of the flash would not be required. Further, the flash/outdoors example sets above give rise to four (4) sets of CDM's. Using a light meter with, say, 4-bit encoding, can provide sixteen (16) models. Also, use of a light meter provides for enhanced reproducability of results and enables the face samples used to generate the models to be taken under laboratory conditions and installation at the time of camera manufacture.

The processing 70 of an image according to a second embodiment is shown in Fig. 6. An input image is provided at step 72 and at step 74 the lighting conditions under which the image was captured are determined. Such a determination may be based on binary data obtained directly from the camera (eg. flash+indoors, no\_flash+outdoors, no\_flash+outdoors, flash+outdoors) or corresponding meta-data provided with, or accompanying, the image, which may be encoded or otherwise communicated according

ţ

10

15

20

to a predetermined format. Once the lighting conditions are determined, a corresponding or closest CDM is selected from a bank of look-up tables 78 retaining the CDM's (60a... 60n) previously determined. At step 80, a first pixel of the input image 72 is selected and at step 82 is tested to see if the (RGB or YUV) colour of the pixel is contained in the selected CDM (60a... 60n).

The steps shown in Fig. 6 following the comparison of step 82 depend upon the manner in which the CDM's are stored. In a preferred implementation, the selected thresholds of step 62 (Fig. 5) are used to construct a binary map or look-up table, where a representative colour vector is represented by a 1 if it is a colour vector that is contained within the thresholded face colour distribution, and by a 0 if the colour vector does not occur in the thresholded colour distribution. Alternatively, the CDM may represent the frequencies of the representative colour vectors of the thresholded colour distribution (ie. the CDM is effectively a histogram of representative colour vectors). A further variation is the case where a sampled distribution is approximated by a parametric model such as a Gaussian or a mixture of Gaussians. In the latter case, the CDM comprises the parameters of the model (eg. mean, co-variance)

As seen in Fig. 6, and according to the preferred implementation, a 1 or 0 value arising from step 82 is added to a map in step 84. Step 86 determines if there are more pixels in the image to be processed and step 88 obtains and passes the next pixel to step 82 for appropriate testing. When all pixels have been tested against the selected CDM, step 90 indicates the result of the preceding steps as being a binary face image map formed using detected skin-coloured pixels.

The map is then subjected at step 92 to further analysis of the skin-coloured pixels to provide at step 94 a face detection map for the image. The further analysis of

20

5

step 92 is, like the first embodiment, preferably independent of considerations of facial colour.

In practice, binary face map formed at step 90 may contain areas where either there are small non-face pixels (0's) surrounded by face pixels (1's), or vice versa. One approach for further analysis according to step 92 is processing the binary face image map so as to set to 0 any pixel locations which are contained in areas that are smaller than the smallest size of a potential face and to set any 0 pixel locations to 1 if they are surrounded by likely face colour pixels. This may be performed using a pair of morphological opening and closing operations with suitably shaped structuring elements.

10 A first structuring element such as:

$$\begin{bmatrix} 0 & 1 & 1 & 0 \\ 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 \\ 0 & 1 & 1 & 0 \end{bmatrix},$$

is used in the opening operation to remove potential face candidate pixel locations below this size. A second structuring element such as:

$$\begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix} ,$$

is used in the closing operation to fill any holes in potential face candidate pixel locations.

Alternative approaches to the use of the structuring elements include using a Hough transform, or to count the number of pixels in the region having skin colour and to threshold that count against a predetermined percentage value. Other methods may be used to perform these tasks.

The result of the process 70 of Fig. 6 is a face detection map of pixel locations in the input image at which a face has been detected, and in all likelihood, a face is present.

,

10

15

20

25

The aforementioned edge detection method of further processing the likely face pixels to determine if a face exits may then be performed on the face detection map 94 resulting from the method 70.

In the preferred embodiment, the face colour distribution models are built for a number of separate lighting conditions, such as flash, non-flash, indoor, outdoor, and the like. However, this technique may be extended to the more general case of arbitrary lighting conditions based directly on parameters obtained from the camera. A list of camera parameters that may be of use in this situation is as follows:

- white balance:
- (ii) white balance mode
- (iii) aperture (iris);
- (iv) shutter speed;
- (v) auto gain control (AGC);
- (vi) auto exposure (AE) mode;
- (vii) gamma;
- (viii) pedestal level; and
- (ix) flare compensation.

The parameters obtained from the camera are preferably obtained from a metadata stream associated with the capture of each image (or video sequence). Examples, of such transmission protocols include IEEE 1394 ("firewire"). Also the ISO standards have defined methods for attaching meta-data to images and video in MPEG-7, MPEG4, and IPEG.

Whilst the first embodiment described with reference to Figs. 1 to 3 divides the image according to regions of substantially homogeneous colour, the second embodiment, and a third embodiment, are not so constrained.

10

15

20

25

The third embodiment is depicted in Fig. 7 by a method 150 where an input image 152 is provided and processed according to steps 154, 156 and 158 corresponding to steps 74, 76 and 78, respectively, of the second embodiment. Once the appropriate CDM has been selected in step 156, step 160 follows to process the input image as one or more regions. As a single region, the entirety of the image is processed on a pixel-by-pixel basis. Alternatively, the input image may be geometrically divided into simple pixel blocks (eg. 25 x 25 pixels, 10 x 20 pixels) which can be formed and processed in raster order. A further alternative, is where the regions, like the first embodiment, are divided on the basis of substantially homogeneous colour.

Step 162 selects a first region to be processed and step 164 a first pixel of that region. Step 166 compares the selected pixel with the CDM in a manner corresponding to step 82 of the second embodiment. Where the pixel matches the model, step 168 increments a count of pixels in the region meeting that criteria. Step 170 determines whether there are any other pixels is the region to be processed and, if so, step 172 obtains the next pixel and returns to step 166 for appropriate testing. When all pixels in the region have been processed, step 174 follows to compare the percentage of pixels classified for the region as skin colour against a predetermined percentage threshold value. Where the percentage is less than the predetermined number, the region is considered a non-face region and step 176 follows to test if there are any more regions to be processed. If so, step 178 selects the next region and returns processing to step 164. The count is then re-set. If not, the method 150 ends at step 184.

Where the percentage exceeds the predetermined percentage, the region is considered a possible face region and step 180 follows to assess the region according to further facial detection analysis. Where such analysis does not detect a face, the method 150 proceeds to step 176 to process any further regions. Where the further

10

15

20

25

analysis of step 180 detects a face, step 182 registers that region as a face region and returns to step 176.

An example of the further analysis able to be performed as a consequence of appropriate marking at step 180 is the edge detection method described above in relation to the first embodiment.

The above described embodiments each indicate that face detection in images may be performed as a two stage process, a first representing something akin to a first filtering of the image to obtain likely candidate pixels or regions, and the second representing more thorough analysis to provide an actual determination on those pixels or regions passed by the first stage. In each case, lighting conditions associated with the capture of the image contribute to the determination performed by the first stage.

The above described methods are preferably practiced using a conventional general-purpose computer system 100, such as that shown in Fig. 4 where the processes of Fig. 3 and/or Figs. 5 and 6 are implemented as software, such as an application program executing within the computer system 100. In particular, the steps of the methods are effected by instructions in the software that are carried out by the computer. The software may be divided into two separate parts; one part for carrying out the above method steps; and another part to manage the user interface between the latter and the user. The software may be stored in a computer readable medium, including the storage devices described below, for example. The software is loaded into the computer from the computer readable medium, and then executed by the computer. A computer readable medium having such software or computer program recorded on it is a computer program product. The use of the computer program product in the computer preferably effects an advantageous apparatus for detecting face candidate regions in accordance with the embodiments of the invention.

the state of the s

5

10

15

20

25

The computer system 100 comprises a computer module 101, input devices such as a keyboard 102 and mouse 103, output devices including a printer 115 and a display device 114. A Modulator-Demodulator (Modem) transceiver device 116 is used by the computer module 101 for communicating to and from a communications network 120, for example connectable via a telephone line 121 or other functional medium. The modem 116 can be used to obtain access to the Internet, and other network systems, such as a Local Area Network (LAN) or a Wide Area Network (WAN), these being possible sources of input images and destinations for detected faces.

The computer module 101 typically includes at least one processor unit 105, a memory unit 106, for example formed from semiconductor random access memory (RAM) and read only memory (ROM), input/output (I/O) interfaces including a video interface 107, and an I/O interface 113 for the keyboard 102 and mouse 103 and optionally a joystick (not illustrated), and an interface 108 for the modern 116. A storage device 109 is provided and typically includes a hard disk drive 110 and a floppy disk drive 111. A magnetic tape drive (not illustrated) may also be used. A CD-ROM drive 112 is typically provided as a non-volatile source of data. The components 105 to 113 of the computer module 101, typically communicate via an interconnected bus 104 and in a manner which results in a conventional mode of operation of the computer system 100 known to those in the relevant art. Examples of computers on which the embodiments can be practised include IBM-PC's and compatibles, Sun Sparcstations or alike computer systems evolved therefrom.

Typically, the application program of the preferred embodiment is resident on the hard disk drive 110 and read and controlled in its execution by the processor 105. Intermediate storage of the program and any data fetched from the network 120 may be accomplished using the semiconductor memory 106, possibly in concert with the hard

15

20

disk drive 110. In some instances, the application program may be supplied to the user encoded on a CD-ROM or floppy disk and read via the corresponding drive 112 or 111, or alternatively may be read by the user from the network 120 via the modem device 116. Still further, the software can also be loaded into the computer system 100 from other computer readable medium including magnetic tape, a ROM or integrated circuit, a magneto-optical disk, a radio or infra-red transmission channel between the computer module 101 and another device, a computer readable card such as a PCMCIA card, and the Internet and Intranets including e-mail transmissions and information recorded on Websites and the like. The foregoing is merely exemplary of relevant computer readable mediums. Other computer readable mediums may be practiced without departing from the scope and spirit of the invention.

The further processing to candidate face images and regions may also be performed by or using the computer system 100 and known arrangements for such processing.

The method of detecting face candidate regions may alternatively be implemented in dedicated hardware such as one or more integrated circuits performing the functions or sub functions of Fig. 3 and/or Figs. 5 and 6. Such dedicated hardware may include graphic processors, digital signal processors, or one or more microprocessors and associated memories.

### Industrial Applicability

It is apparent from the above that the embodiments of the invention are applicable in fields such as content-based image retrieval, personal identification or verification for use with automatic teller machines or security cameras, or automated interaction between humans and computational devices.

The foregoing describes only some embodiments of the present invention, and modifications and/or changes can be made thereto without departing from the scope and spirit of the invention as defined in the claims.

20

### WE CLAIM:

- A method of detecting a face in a colour digital image, said method comprising the steps of:
- 5 (i) segmenting said image into a plurality of regions each having a substantially homogenous colour:
  - (ii) testing the colour of each said region created in step (i) to determine those regions having predominantly skin colour; and
- (iii) subjecting only the regions determined in step (ii) to further facial 10 feature analysis whereby said regions created in step (i) not having a predominantly skin colour are not subjected to said further feature analysis.
  - The method as claimed in claim 1 including the further step of using in step (ii) a colour distribution model utilising previously sampled data.
  - The method as claimed in claim 1 including the further step of using chromatic colours derived from RGB values in step (ii).
  - 4. The method as claimed in claim 1 wherein said image is from a camera.
  - The method as claimed in claim 4 wherein a particular image is selected from the group consisting of images taken with use of a flash, and images taken without use of a flash.

ŝ

- The method as claimed in claim 1 wherein the further facial analysis in step (iii) is independent of facial colour.
- The method as claimed in claim 5 wherein the further facial analysis comprises edge detection.
- 8. The method as claimed in claim 6 wherein said edge detection utilises an edge detection filter comprising second derivative Gaussian function in a first direction substantially orthogonal to the edge to be detected and a Gaussian function in a second direction substantially orthogonal to said first direction.
- The method as defined in claim 6 or 7 wherein further facial analysis is carried out utilising the spatial relationship of detected edges.
- 10. The method as defined in claim 1 wherein step (i) includes growing a region by determining the average colour of a group of pixels, determining the difference between the average colour of the group and the average colour of pixels adjacent to the group, and, if the colour difference is less than a predetermined threshold, adding the adjacent pixels to the group.

5

10

15

 Apparatus for detecting a face in a colour digital image, said apparatus comprising.

segmenting means to segment said image into a plurality of regions each having a substantially hômogeneous colour,

colour detecting means coupled to said segmenting means to determine those regions having predominantly skin colour.

analysis means coupled to said colour detection means to subject only those regions having predominantly skin colour to a facial feature analysis.

5

- 12. The apparatus as claimed in claim 11 wherein said colour detection means includes a colour distribution model and storage means storing previously sampled data for use in said colour distribution model.
- 10 13. The apparatus as claimed in claim 12 including chromatic colour calculations means to derive from RGB values of said image, chromatic colour values.
  - The apparatus as claimed in claim 11 wherein said image is from a camera.

15

15. The apparatus as claimed in claim 11 wherein the particular image is selected from the group consisting of images taken with use of a flash, and images taken without use of a flash.

1.

- 16. The apparatus as claimed in claim 11 wherein said facial feature analysis of said analysis means is independent of facial colour.
- 20 ar
  - 17. The apparatus is claimed in claim 10 wherein said analysis means includes an edge detector to detect edges in the image.

1

18. The apparatus as claimed in claim 17 wherein said analysis means has an edge detection filter comprising second derivative Gaussian function in a first direction substantially orthogonal to the edge to be detected and a Gaussian function in a second direction substantially orthogonal to said first direction.

5

19. The apparatus as claimed in claim 17 wherein said analysis means includes a spatial determinator to determine the spatial relationship of detected edges.

10

20. The apparatus as claimed in claim 11 including an accumulator means and a colour difference means to determine the difference between the average colour of a group of pixels and the average colour of pixels adjacent to that group, since that if the colour distance is less than a predetermined threshold, said adjacent pixels are added to said accumulator means to thereby grow a region.

15

21. A computer readable medium incorporating a computer program product for detecting a face in a colour digital image, said computer program product including a sequence of computer implementable instructions for carrying out the steps of:

segmenting said image into a plurality of regions each having a

20

(ii) testing the colour of each said region created in step (i) to determine those regions having predominantly skin colour; and

(iii) subjecting only the regions determined in step (ii) to further facial feature analysis whereby said regions created in step (i) not having a predominantly skin colour are not subjected to said further feature analysis.

25

(i)

substantially homogenous colour:

20

- 22. The medium as claimed in claim 21 including the further step of using in step (ii) a colour distribution model utilising previously sampled data
- The medium as claimed in claim 21 including the further step of using chromatic
   colours derived from RGB values in step (ii).
  - 24. The medium as claimed in claim 21 wherein said image is from a camera.
- 25. The medium as claimed in claim 21 wherein the particular image is selected 10 from the group consisting of images taken with use of a flash, and images taken without use of a flash.
  - 26. The method as claimed in claim 21 wherein the further facial analysis in step (iii) is independent of facial colour.
  - 27. The medium as claimed in claim 26 wherein the further facial analysis comprises edge detection.
  - 28. The medium as claimed in claim 27 wherein said edge detection utilises an edge detection filter comprising second derivative Gaussian function in a first direction substantially orthogonal to the edge to be detected and a Gaussian function in a second direction substantially orthogonal to said first direction.
- The medium as defined in claim 26 wherein further facial analysis is carried out
   utilising the spatial relationship of detected edges.

10

15

20

- 30. The medium as defined in claim 21 wherein step (i) includes growing a region by determining the average colour of a group of pixels, determining the difference between the average colour of the group and the average colour of pixels adjacent to the group, and, if the colour difference is less than a predetermined threshold, adding the adjacent pixels to the group.
- 31. A method of detecting a face in a colour digital image formed of a plurality of pixels, said method comprising the steps of:
- (i) testing the colour of said pixels to determine those said pixels having predominantly skin colour, said testing utilising at least one image capture condition provided with said image; and
- (ii) subjecting only said those pixels determined in step (i) as having predominantly skin colour to further facial feature analysis whereby those said pixels not having a predominantly skin colour are not subjected to said further facial feature analysis.
- 32. A method according to claim 31 wherein each said image capture condition is acquired at a time said image is captured.
- 33. A method according to claim 32 wherein said image is encoded according to a predetermined format and said at least one image capture condition is represented as meta-data associated with said format.

۰

15

- 34. A method according to claim 31 wherein said at least one image capture condition comprises lighting conditions at a time said image was captured.
- 35. A method according to claim 31 wherein step (i), comprises the sub-step, preceding said testing, of:
  - (a) dividing said image into a plurality of regions, each said region comprising a plurality of said pixels; and

wherein said testing is performed on pixels within each said region to determine those ones of said regions that are predominantly skin colour and step (ii) comprises performing said further facial feature analysis on only those said regions determined to be predominantly of skin colour.

- 36. A method according to claim 31 wherein step (i) utilises at least one predetermined colour distribution model, said model having been generated using previously sampled facial image data.
- 37. A method according to claim 36 wherein said colour distribution model is generated for a particular image capture device.
- 20 38. A method according to claim 36 wherein separate colour distribution models are generated for said different image capture conditions.
  - 39. A method according to claim 38 wherein said at least one image capture condition comprises lighting conditions at a time said image was captured and separate

20

25

5

colour models are generated for different lighting conditions at a time said previously sampled facial image data was captured.

- 40. A method according to claim 39 wherein separate colour distribution models are generated for groups of images taken with a flash and images taken without a flash.
- 41. A method according to claim 39 wherein separate colour distribution models are generated for groups of images taken indoors and images taken outdoors.
- 42. A method according to claim 36 wherein each said colour distribution model is represented as a frequency histogram of colour representation vectors.
  - 43. A method according to claim 36 wherein each said colour distribution model is represented as a probability distribution of colour representation vectors.
  - 44. A method according to claim 36 wherein each said colour distribution model is represented as a binary map of colour representation vectors.
  - 45. A method according to claim 42, 43 or 44 wherein said colour representation vectors are derived from perceptual colour space values of the predetermined skin-colour pixels in said previously sampled facial image data.
    - 46. A method according to claim 42, 43 or 44 wherein said colour representation vectors contain ichromatic colour values derived from those RGB values of the predetermined skin-colour pixels in said previously sampled facial image data.

47. A method according to claim 44 wherein said binary map comprises a percentage of the skiu colour pixels that were identified in said previously sampled facial image data.

5

48. A method according to claim 47 wherein one of said pixels is classified as being skin colour if the colour representation vector corresponding thereto occurs within said binary map.

10

49. A method according to claim 42 wherein each of said pixels is classified as being skin colour if the frequency of the colour representation vector corresponding thereto exceeds a predetermined threshold frequency.

15

50. A method according to claim 44 wherein each of said pixels is classified as being skin colour if the probability of the colour representation vector corresponding thereto exceeds a predetermined probability threshold.

51. A method according to claim 48 wherein one said regions is determined to be predominantly skin colour if more than a predetermined percentage of the total number of said pixels in said one region are classified as being skin colour.

20

52. A method according to claim 35 wherein said regions are geometrically divided from said image.

ŝ

20

25

- 53. A method according to claim 35 wherein said regions are formed of pixels having substantially homogenous colour
- 54. A method according to claim 53 wherein said regions are formed using a region
   5 growing method based upon colour differences.
  - 55. A method according to claim 35 wherein said further analysis of step (ii) is independent of face colour.
- 10 56. Apparatus for detecting a face in a colour digital image formed of a plurality of pixels, said apparatus comprising:

means for testing the colour of said pixels to determine those said pixels having predominantly skin colour, said testing utilising at least one image capture condition provided with said image: and

means for subjecting only said those pixels so determined as having predominantly skin colour to further facial feature analysis whereby those said pixels not having a predominantly skin colour are not subjected to said further facial feature analysis.

- Apparatus according to claim 56 wherein each said image capture condition is acquired at a time said image is captured.
  - 58. Apparatus according to claim 57 wherein said image is encoded according to a predetermined format and said at least one image capture condition is represented as meta-data associated with said format.

10

15

20

25

59. Apparatus according to claim 56 wherein said at least one image capture condition comprises lighting conditions at a time said image was captured.

60. Apparatus according to claim 56 wherein said means for testing comprises means for dividing said image into a plurality of regions, each said region comprising a phrality of said pixels:

wherein said means for testing operates on pixels within each said region to determine those ones of said regions that are predominantly skin colour and said means for subjecting cause said further facial feature analysis to be performed on only those said regions determined to be predominantly of skin colour.

61. A computer readable medium incorporating a computer program product for detecting a face in a colour digital image formed of a plurality of pixels, said computer program product comprising:

means for testing the colour of said pixels to determine those said pixels having predominantly skin colour, said testing utilising at least one image capture condition provided with said image; and

means for subjecting only said those pixels so determined as having prodominantly skin colour to further facial feature analysis whereby those said pixels not having a predominantly skin colour are not subjected to said further facial feature analysis.

62. A computer readable medium according to claim 61 wherein each said image capture condition is acquired at a time said image is captured.

63. A computer readable medium according to claim 62 wherein said image is encoded according to a predetermined format and said at least one image capture condition is represented as meta-data associated with said format.

5

- 64. A computer readable medium according to claim 61 wherein said at least one image capture condition comprises lighting conditions at a time said image was captured.
- 65. A computer readable medium according to claim 61 wherein said means for testing comprises means for dividing said image into a plurality of regions, each said region comprising a plurality of said pixels;

wherein said means for testing, operates on pixels within each said region to determine those ones of said regions that are predominantly skin colour and said means for subjecting cause said further facial feature analysis to be performed on only those said regions determined to be predominantly of skin colour.

### Abstract

### FACE DETECTION IN DIGITAL IMAGES

5 The present invention relates to the detection of faces in digital images. Rather than subjecting the entire image (1) to computationally intensive face detection analysis, the image is subjected to computationally simple analysis to identify candidate pixels likely to be of skin colour. Only those pixels having such colour, which may be determined in a number of ways, are subject to computationally intensive face detection analysis. The image is preferably divided into regions (2) each of which is then analysed for features indicative of skin colour. The simple analysis is based on lighting conditions associated with the capture of the image and preferably utilizes the selection of one of a number of skin colour models associated with a range of lighting conditions.




Fig. 1




Fig. 2

- 1




Fig. 3




Fig. 4




Fig. 5





Fig. 6



CFP1327AUA IPR20A 461584D1

ter est series procession from the green plants factor in procession and perfect the series and perfect the series from the series and the series are the series and the series and the series are the series and the series and the series are the series and the series and the se

[I:\CISRA\IPR\IPR20A] 461584D1.fm

09/326,561

## COMBINED DECLARATION AND POWER OF ATTORNEY FOR C-LP PATENT APPLICATION

As a below named inventor, I hereby declare that.

My residence, post office address and citizenship are as stated below next to my name.

I believe I a	am the original, first and sole	inventor (if only one name is listed below	w) or an original, first and joint
inventor (if plural na	ames are listed below) of the	subject matter which is claimed and for	which a patent is sought on the
invention entitled F.	ACE DÉTECTION IN DIGI	the specification of which is	
X attached here	towas filed on		
as Application No		and was amended on	
(if applicable).			
I hereby st	ate that I have reviewed and ded by any amendment refer	understand the contents of the above-ide red to above.	ntified specification, including
I acknowle	edge the duty to disclose info	rmation which is material to patentability	y as defined in 37 CFR §1.56.
patent or inventor's	certificate listed below and h	ander Title 35, United States Code, §119 of ave also identified below any foreign application on which priority is claimed	olication for patent or inventor's
Country	Application No.	Filed (Day/Mo./Yr.)	(Yes/No) Priority Claimed
AUSTRALIA	PP4009	10 June 1998	YES
below and, insofar application in the n	as the subject matter of each nanner provided by the first information as defined in Tit	35, United States Code, §120 of any Un of the claims of this application is not dis- paragraph of Title 35, United States Cod lea 37, Code of Federal Regulations, §1.5t nad or PCT international filing date of th  Status (Patented/Pend	closed in the prior United States e §112, I acknowledge the duty b(a) which occurred between the is application:
••		Pending	,
09/326 561	07 June 1999	Pending	

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

### FITZPATRICK, CELLA, HARPER & SCINTO Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

# COMBINED DECLARATION AND POWER OF ATTORNEY FOR C-I-P PATENT APPLICATION (Page 2)

	Citizen/Subject of AUSTRALIA	
	enwood, New South Wales 2768, Australia	
	KABUSHIKI KAISHA	
	a-ku, Tokyo, Japan	
70-2, Shiftoniarako 5 chome, Shi	1 Aug 101/01/04/04	
Full Name of Second Joint Invento	or, if any <u>ALISON JOAN LENNON</u>	
Second Inventor's signature		
Date	Citizen/Subject of GREAT BRITAIN	
	main, New South Wales 2041, Australia	
Post Office Address c/o CANON	KABUSHIKI KAISHA	
	a-ku, Tokyo, Japan	
Full Name of Third Joint Inventor	, if any ANDREW PETER BRADLEY	
Third Inventor's signature		
Date	Citizen/Subject of AUSTRALIA	
Residence 68 The Bulwark, Castle	ecrag, New South Wales 2068 Australia	
Post Office Address c/o CANON	KABUSHIKI KAISHA	
30-2, Shimomaruko 3-chome, Oht	ta-ku, Tokyo, Japan	
Full Name of Fourth Joint Invento	or, if any	
Fourth Inventor's signature		
Date	Citizen/Subject of	
Residence		
Post Office Address		
	, if any	
Fifth Inventor's signature		
Fifth Inventor's signature Date	Citizen/Subject of	
Fifth Inventor's signature  Date Residence	Citizen/Subject of	
Fifth Inventor's signature  Date Residence	Citizen/Subject of	
Fifth Inventor's signature  Date Residence	Citizen/Subject of	
Fifth Inventor's signature  Date Residence Post Office Address	Citizen/Subject of	
Fifth Inventor's signature  Date  Residence  Post Office Address  Full Name of Sixth Joint Inventor	Citizen/Subject of r, if any	
Fifth Inventor's signature	Citizen/Subject of r, if any	

/PAP